



## Activated Carbon JZ- ACW

### Description:

JZ-ACW activated carbon has the characteristics of developed pores, fast adsorption speed, large specific surface area, high strength, anti friction, washing resistance, etc.

### Applications:

Widely used in petrochemical, electric water, drinking water, residual chlorine removal, gas adsorption, flue gas desulfurization, gas separation, impurity removal and odor removal. It is suitable for food brewing, antiseptis, electronic industry, catalyst carrier, oil refinery and gas mask.

### Specification:

Specification	Unit	JZ-ACW4	JZ-ACW8
Diameter	Mesh	4*8	8*20
Iodine adsorption	≥%	950	950
Surface Area	≥m <sup>2</sup> /g	900	900
Crush Strength	≥%	95	90
Ash Content	≤%	5	5
Moisture Content	≤%	5	5
Bulk Density	kg/m <sup>3</sup>	520±30	520±30
PH	/	7-11	7-11

### Standard Package:

25 kg/woven bag

### Attention:

The product as desiccant cannot be exposed in the open air and should be stored in dry condition with air-proof package.

**CÔNG TY TNHH TM & DV CH VIỆT NAM**

VP Giao Dịch : Số 73C/291/42 - Lạc Long Quân - Nghĩa Đô - Cầu Giấy - HN

Trạm bảo hành 24/7: Số 12 ngõ 190/5 - Thanh Am - Long Biên Hà Nội

CN Miền Nam: 150/10 - HT13, KP2, Hiệp Thành , Quận 12, Tp. Hồ Chí Minh

Điện thoại: 024.6.6868.111

Hotline: 0909.514.123

